

SPECIFICATIONS

HARDWARE SPECIFICATIONS

SignCo EDS only guarantee's that DsignXpress software will work on computers supplied by SignCo EDS. The Following requirements are needed in order to run DsignXpress software. Please keep in mind if you are supplying your own computer that even though these specifications should enable you to use your own computer, we cannot guarantee 100% compatibility.

Also listed are the additional requirements needed for the specific type of interface that you will be using to communicate to the sign. If you have any questions on which setup you are receiving contact you local dealer .

| | |
|-------------------|--|
| Operating System: | W indows 2000 or XP |
| Disk Space: | 20 Meg minimum |
| Memory | 256 MB minimum, 512 MB recomended |
| CD ROM Drive: | Required |
| Processor: | 1GHZ Pentium III or better |
| Display: | Direct X 8.0 supported adapter |
| Pointer: | W indows Compatible Device |
| Network: | Software can be installed on a network drive |

V4 RS232 SIGN CONTROLLER

Serial Ports: Com1 through Com 20
Baud Rates: Standard 38.4K Baud or less

V4 RADIO LINK CONTROLLER

Serial Ports: Com1 through Com 20
Baud Rates: Standard 38.4K Baud or less
Modem: Cirronet HN210 (supplied)

V4 REMOTE SIGN CONTROLLER

Serial Ports: Com1 through Com 20
Baud Rates: 38.4K Baud
Modem: Hayes compatible

V4 CONTROLLER - ETHERNET CONNECTION

Network: Any standard Ethernet (NIC)
10mbs or 10/100mbs with
TCP/IP

Protocols: TCP/IP. RAW TCP connection
to port 3001

Serial Speed: 38.4K Standard

Device Server: MSS-100 Serial Server

Software: COM Port Redirector (emulates
a standard com port)

TECHNICAL SUPPORT

For more infomation, product support or additional training using the DsignXpress software, in the United States call (800) 445-9206, outside of the United States call (308) 384-6860.